


# MCLM020 Pluggable PCB Connector, Plug



MC

## DIMENSIONS/POSITIONS

## MCLM020-508

間距	Pitch	5.08mm
位數	Poles	32Poles
塑膠本體	Housing Material	PA 66
壓線圈	Cage Clamp	Brass, Ni Plated
導電夾片	Contact	Phosphor Bronze, Tin Plated
螺紋	Screw Thread	M3.0, Steel, Zinc Plated
電線線徑	Wire Size	14 ~ 22AWG
剝線長度	Wire Strip Length	7mm ~ 8mm
最大緊固扭矩	Tightening Torque, Max.	5.22 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C

## TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE		
額定電流 I <sub>n</sub> Nominal Current I <sub>n</sub>	5A	
額定橫截面 Nominal Cross Section	1.5mm <sup>2</sup>	
最大負載電流 Maximum load current	5A	
絕緣材料 Insulating Material	PA	
阻燃等級,符合UL94 Inflammability class acc. to UL94	V0	
額定電壓,UL/CUL Nominal voltage, UL/CUL	300V	
額定電流,UL/CUL Nominal current, UL/CUL	5A	

